Technical Data Sheet



Hicrete Powder Release Agent

Product Description:

Hicrete Powder Release pre-blended parting agent used for stamping concrete. Power Release is a blend of calcium, sterates and UV resistant iron oxide pigments. It is available in Neutral or Pre-Colored to match any color on the color chart. Pre-blending promotes product uniformity and color consistency. Because of the unusual characteristics of this formulation, it may be used for many different applications.

Product Uses:

Hicrete Power Release is used to keep stamping tools from sticking to the still plastic concrete surface. The product can be used for variety of applications such as stamped concrete, landscape curbing, vertical applications and more. Because the product is available pre-colored, it allows contractors to add accent colors during the initial stamping process. Neutral can be used if no additional color is desired.

Mixing Instruction:

No mixing necessary, simply fluff material in the pail before using.

Application:

The Powder Release is to be applied after all the trowel work is completed. Do not trowel into the concrete surface. After all of the bleed water is gone and all trowel work is completed, cast a thin film of Powder Release across the surface. Stamp the surface with the desired pattern. Allow the concrete surface to dry completely for 48 hours. Using a hose or pressure washer, remove the excess release. Be sure to remove a uniform amount across the entire project. The color that you see when the surface is wet with water is what is will look like when sealed. If additional colors are desired or color adjustment is needed, antique with Color Wash.

Coverage:

800-1000 Sq/Ft per 11.35 Kg Bag

Sefety Precautions:

Do not inhale, wear a dust mask. Wear eye protection, avoid contact with eyes.





Technical Data Sheet



Hicrete Powder Release Agent

Limited Warranty:

This product is warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over its use, no warranty expressed or implied, is made as to the effect of such use. Seller's and Manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.

